## **SDX** THERMOBOX





| GUIDES   | WEIGHT                            | EFFECT                  | EXTERIOR WALLS:   | ABS plastic.   |
|--|-----------------------------------|-------------------------|---|--|
| 14+14 x GN 1/1<br>80mm spacing                                   | 126kg                             | Neutral +<br>230V/1000W | INNER CONTAINER:  | Welded container in stainless steel.   |
| OUTER INNER S INNER F  |                                   | GUIDES:                 | Stainless steel, pressed from the inner container.  Maximum load per pair of guides is 30 kg. |  |
| W: 930mm<br>D: 770mm<br>H: 1515mm                                | W: 330mm<br>D: 540mm<br>H: 1160mm |                         | INSULATION:   | Polyurethane.  |
| ADDITIONAL INFORMATION   |                                   |                         | DOOR:   | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. |
| Additional pull handles on the sides, at the back, are included. |                                   |                         | WHEELS:   | 160 mm wheels, two brakeable and two fixed.  |
| PRODUCT NUMBER   |                                   |                         | TOP FRAME:  | A stable and protective frame with PVC corners.  |
| 122067-ZSF<br>SDX Thermobox SF420 (14+14 GN 1/1) One grip handle |                                   |                         | TROLLEY FRAME:  | Reject list of stainless steel coated with PVC.  |
|  |                                   |                         | S:  | Neutral, insulation class IP55.  |
|  |                                   |                         | F:  | Efficient convection heating system, with electronic temperature control. IP55 rated.  |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT