



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
14 x GN 1/1 80mm spacing	83 kg	230V/190W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER		GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
B: 525mm D: 770mm H: 1735mm	W: 330mm D: 540mm H: 1160mm		INSULATION:	Polyurethane.
ADDITIONAL INFORMATION			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
Additional pull handles on the sides, at the back, are included.			WHEELS:	160 mm wheels, two brakeable and two fixed.
PRODUCT NUMBER			TOP FRAME:	A stable and protective frame with PVC corners.
122209-ZK SDX Thermobox K210 ECO (14 GN 1/1) One grip handle			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
122209-XK SDX Thermobox K210 ECO (14 GN 1/1) Eccentric lock			K:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT