



TRAYSERVE F8

BASED ON THE STANDARD F180 MODEL



GUIDES	WEIGHT	EFFECT	TEMPERATURE RANGE:
8 x GN 1/1 115mm spacing	57kg	230V/1000W	40 - 90°C
OUTER	INNER		EXTERIOR WALLS: ABS plastic.
W: 525mm D: 770mm H: 1355mm	W: 330mm D: 540mm H: 1000mm		INNER CONTAINER: Welded container in stainless steel.
PRODUCT NUMBER			GUIDES: Aluminium, riveted to inner container
122952-ZTS SDX®THERMOBOX® Trayserve F8 (8 GN 1/1 115D) One grip handle			INSULATION: Polyurethane.
			DOOR: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS: 160 mm wheels, two brakeable and two fixed.
			TOP FRAME: A stable and protective frame with PVC corners.
			TROLLEY FRAME: Impact protection bumper of stainless steel coated with PVC.
			F: Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT