



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	
4+4 x GN 1/1 80mm spacing	170kg	Neutral + 230V/550W	ABS plastic.	
OUTER	INNER S	INNER F	INNER CONTAINER:	
W: 525mm D: 770mm H: 1310mm	W: 330mm D: 540mm H: 350mm	W: 330mm D: 540mm H: 350mm	Welded container in stainless steel.	
<b>PRODUCT NUMBER</b>			GUIDES:	
<b>122071-ZSF</b> SDX Thermobox SF120 (4+4 GN 1/1) One grip handle  <b>122071-XSF</b> SDX Thermobox SF120 (4+4 GN 1/1) Eccentric lock			Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.	
			INSULATION:	Polyurethane.
			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS:	160 mm wheels, two brakeable and two fixed.
			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			S:	Neutral, insulation class IP55.
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT