



KF420 ECO



GUIDES	WEIGHT	EFFECT	TEMPERATURE RANGE:
14+14 x GN 1/1 80mm spacing	145kg	230V/190W AC + 230V/1000W	K: 1 - 9°C F: 40 - 90°C
OUTER	INNER K	INNER F	EXTERIOR WALLS:
W: 930mm D: 770mm H: 1735mm	W: 330mm D: 540mm H: 1160mm	W: 330mm D: 540mm H: 1160mm	ABS plastic.
ADDITIONAL INFORMATION			INNER CONTAINER:
Additional pull handles on the sides, at the back, are included.			Welded container in stainless steel.
PRODUCT NUMBER			GUIDES:
122226-ZKF SDX Thermobox KF420 ECO (14+14 GN 1/1) One grip handle			Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
			INSULATION:
			Polyurethane.
			DOOR:
			Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS:
			160 mm wheels, two brakeable and two fixed.
			TOP FRAME:
			A stable and protective frame with PVC corners.
			TROLLEY FRAME:
			Impact protection bumper of stainless steel coated with PVC.
			K:
			Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated
			F:
			Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT