



K90 ECO *



GUIDES		WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
6 x GN 1/1 80mm spacing		70 kg	230V/190W	INNER CONTAINER:	Welded container in stainless steel.
OUTER		INNER		GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 770mm H: 1085mm		B: 330mm D: 540mm H: 510mm		INSULATION:	Polyurethane.
PRODUCT NUMBER				DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122207-ZK SDX Thermobox K90 ECO (6 GN 1/1) One grip handle				WHEELS:	160 mm wheels, two brakeable and two fixed.
122207-XK SDX Thermobox K90 ECO (6 GN 1/1) Eccentric lock				TOP FRAME:	A stable and protective frame with PVC corners.
				TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
				K:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT