



EASY2SERVE CE240



| GUIDES | WEIGHT | EFFECT | EXTERIOR WALLS: | ABS plastic. |
|--|----------------------------------|----------------------------------|------------------|--|
| 8+8 x GN 1/1 80mm spacing | 97kg | AA 230V/245W + 230V/650W | INNER CONTAINER: | Welded container in stainless steel. |
| OUTER | INNER C | INNER E | GUIDES: | Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg. |
| W: 930mm D: 825mm H: 1380mm | W: 330mm D: 540mm H: 670mm | W: 330mm D: 540mm H: 670mm | INSULATION: | Polyurethane. |
| ADDITIONAL INFORMATION | | | DOOR: | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. |
| <p>A tray lane is located on the front and two tray stands are located on the sides. It is equipped with a stainless steel plating area on top, as well as a stainless steel top shelf with an integrated LED-light. Additional handles are located on both sides.</p> | | | WHEELS: | 160 mm wheels, two brakeable and two fixed. |
| | | | TROLLEY FRAME: | Reject list of stainless steel coated with PVC. |
| PRODUCT NUMBER | | | C: | Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55. |
| <p>122805 SDX Thermobox EASY2SERVE CE240 (8+8 GN 1/1). One grip handle</p> | | | E: | Patented, efficient heating system, with electronic temperature control. Foil elements, insulation class IP55. |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT