

# SDX® THERMOBOX®

# F60



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
4 x GN 1/1 80mm spacing	41kg	230V/550W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER		GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 770mm H: 895mm	W: 330mm D: 540mm H: 350mm		INSULATION:	Polyurethane.
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
<b>122006-ZF</b> SDX Thermobox F60 (4 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
<b>122006-XF</b> SDX Thermobox F60 (4 GN 1/1) Eccentric lock			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT