



| | | | | | | | | | | |
|--|--|--|----------------------------------|--|--|----------------------------------|--|--|---|--|
| GUIDES | | | WEIGHT | | | EFFECT | | | EXTERIOR WALLS: ABS plastic. | |
| 4+6 x GN 1/1 80mm spacing | | | 70kg | | | AA120/245W + 230V/550W | | | INNER CONTAINER: Welded container in stainless steel. | |
| OUTER | | | INNER K | | | INNER F | | | GUIDES: Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg. | |
| W: 525mm D: 830mm H: 1285mm | | | W: 330mm D: 540mm H: 350mm | | | W: 330mm D: 540mm H: 510mm | | | INSULATION: Polyurethane. | |
| PRODUCT NUMBER | | | | | | | | | DOOR: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. | |
| 122282-ZCF SDX Thermobox CF150 (4+6 GN 1/1) One grip handle | | | | | | | | | WHEELS: 160 mm wheels, two brakeable and two fixed. | |
| 122282-XCF SDX Thermobox CF150 (4+6 GN 1/1) Eccentric lock | | | | | | | | | TOP FRAME: A stable and protective frame with PVC corners. | |
| | | | | | | | | | TROLLEY FRAME: Reject list of stainless steel coated with PVC. | |
| | | | | | | | | | C: Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55. | |
| | | | | | | | | | F: Efficient convection heating system, with electronic temperature control. IP55 rated. | |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT