



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
4+4 x GN 1/1 80mm spacing	54kg	2 x 230V/280W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER		GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 710mm H: 1310mm	W: 330mm D: 540mm H: 350+350mm		INSULATION:	Polyurethane.
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122013-ZE SDX Thermobox EE120 (4+4 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
122013-XE SDX Thermobox EE120 (4+4 GN 1/1) Eccentric lock			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			E:	Patented, efficient heating system, with electronic temperature control. Foil elements, insulation class IP55.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT