PRODUCTSHEET SDX® THERMOBOX® F-SERIES REV. 20230705SDX







| GUIDES                            | WEIGHT                           | EFFECT    |
|-----------------------------------|----------------------------------|-----------|
| 8 x GN 1/1<br>80mm spacing        | 49kg                             | 230V/550W |
| OUTER                             | INNER                            |           |
| W: 525mm<br>D: 770mm<br>H: 1215mm | W: 330mm<br>D: 540mm<br>H: 670mm |           |
| PRODUCT NUMBER                    |                                  |           |

## 122027-ZF

SDX Thermobox F120 (8 GN 1/1) One grip handle

## 122027-XF

SDX Thermobox F120 (8 GN 1/1) Eccentric locke

| EXTERIOR WALLS:  | ABS plastic.  |
|------------------|---|
| INNER CONTAINER: | Welded container in stainless steel.  |
| GUIDES:          | Stainless steel, pressed from the inner container.  Maximum load per pair of guides is 30 kg. |
| INSULATION:      | Polyurethane.   |
| DOOR:            | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.        |
| WHEELS:          | 160 mm wheels, two brakeable and two fixed.   |
| TOP FRAME:       | A stable and protective frame with PVC corners.   |
| TROLLEY FRAME:   | Reject list of stainless steel coated with PVC.   |
| F:               | Efficient convection heating system, with electronic temperature control. IP55 rated.         |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT

