





GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
8+8 x GN 1/1	90kg	Neutral + 230V/1000W		
80mm spacing			INNER CONTAINER:	Welded con
OUTER	INNER S	INNER F	GUIDES:	Stainless ste Maximum lo
W: 930mm	W: 330mm	W: 330mm		
D: 770mm	D: 540mm	D: 540mm	INSULATION:	Polyurethan
H: 1215mm	H: 670mm	H: 670mm		
PRODUCT NUMBER			DOOR:	Internal surfa
122066-ZSF			WHEELS:	160 mm whe
SDX Thermobox SF	240 (8+8 GN 1/1) One o	grip handle		

EXTERIOR WALLS:	ABS plastic.		
INNER CONTAINER:	Welded container in stainless steel.		
GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.		
INSULATION:	Polyurethane.		
DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.		
WHEELS:	160 mm wheels, two brakeable and two fixed.		
TOP FRAME:	A stable and protective frame with PVC corners.		
TROLLEY FRAME:	Reject list of stainless steel coated with PVC.		
S:	Neutral, insulation class IP55.		
F:	Efficient convection heating system, with electronic temperature control. IP55 rated.		

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT