## 

## F150 III



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
10 x GN 1/1 80mm spacing	61kg	230V/1000W	ADS plastic.	
			INNER CONTAINER:	Welded container in stainless steel.
OUTER INNER				Stainless steel, pressed from the inner container.
W: 525mm	W: 330mm D: 540mm H: 830mm		GUIDES:	Maximum load per pair of guides is 30 kg.
D: 770mm			INSULATION:	Polyurethane.
H: 1080mm				
PRODUCT NUMBER			DOOR: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.	
122064-ZF				
SDX Thermobox F150 (10 GN 1/1) One grip handle			WHEELS:	
122064-XF SDX Thermobox F150 (10 GN 1/1) Eccentric lock				160 mm wheels, two brakeable and two fixed.
			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			F:	Efficient convection heating system, with electronic temper- ature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT