



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:
6+6 x GN 1/1 80mm spacing	62kg	Neutral + 230V/550W	ABS plastic.
OUTER	INNER S	INNER F	INNER CONTAINER:
W: 525mm D: 770mm H: 1445mm	W: 330mm D: 540mm H: 510mm	W: 330mm D: 540mm H: 510mm	Welded container in stainless steel.
<b>PRODUCT NUMBER</b>  <b>122105-ZSF</b> SDX Thermobox SF180 (6+6 GN 1/1) One grip handle  <b>122105-XSF</b> SDX Thermobox SF180 (6+6 GN 1/1) Eccentric lock			GUIDES:
			Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
			INSULATION:
			Polyurethane.
			DOOR:
			Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS:
			160 mm wheels, two brakeable and two fixed.
			TOP FRAME:
			A stable and protective frame with PVC corners.
TROLLEY FRAME:			
Reject list of stainless steel coated with PVC.			
S:			
Neutral, insulation class IP55.			
F:			
Efficient convection heating system, with electronic temperature control. IP55 rated.			

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT