

F90 III



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
6 x GN 1/1 80mm spacing	45 kg	230V/550W		
			INNER CONTAINER:	Welded container in stainless steel.
OUTER INNER				Stainless steel, pressed from the inner container.
W: 525mm	W: 330mm D: 540mm H: 510mm		GUIDES:	Maximum load per pair of guides is 30 kg.
D: 770mm			INSULATION:	Polyurethane.
H: 1055mm				
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122004-ZF				
SDX Thermobox F90 (6 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
122004-XF SDX Thermobox F90 (6 GN 1/1) Eccentric lock				
			TOP FRAME:	A stable and protective frame with PVC corners.
		TROLLEY FRAME:	Reject list of stainless steel coated with PVC.	
			F:	Efficient convection heating system, with electronic temper- ature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT