



| GUIDES | WEIGHT | EFFECT | EXTERIOR WALLS: | ABS plastic. |
|--|----------------------------------|----------------------------------|------------------|---|
| 4+8 x GN 1/1 80mm spacing | 75kg | AA120/245W + 230V/550W | INNER CONTAINER: | Welded container in stainless steel. |
| OUTER | INNER K | INNER F | GUIDES: | Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg. |
| W: 525mm D: 830mm H: 1445mm | W: 330mm D: 540mm H: 350mm | W: 330mm D: 540mm H: 670mm | INSULATION: | Polyurethane. |
| PRODUCT NUMBER | | | DOOR: | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. |
| 22284-ZCF SDX Thermobox CF180 (4+8 GN 1/1) One grip handle | | | WHEELS: | 160 mm wheels, two brakeable and two fixed. |
| 122284-XCF SDX Thermobox CF180 (4+8 GN 1/1) Eccentric lock | | | TOP FRAME: | A stable and protective frame with PVC corners. |
| | | | TROLLEY FRAME: | Reject list of stainless steel coated with PVC. |
| | | | C: | Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55. |
| | | | F: | Efficient convection heating system, with electronic temperature control. IP55 rated. |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT