



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
4+6 x GN 1/1 80mm spacing	56kg	Neutral + 230V/650W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER S	INNER E	GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 710mm H: 1285mm	W: 330mm D: 540mm H: 350mm	W: 330mm D: 540mm H: 510mm	INSULATION:	Polyurethane.
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122060-ZSE SDX Thermobox SE150 (4+6 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
122060-XSE SDX Thermobox SE150 (4+6 GN 1/1) Eccentric lock			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			S:	Neutral, insulation class IP55.
			E:	Patented, efficient heating system, with electronic temperature control. Foil elements, insulation class IP55.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT