



GUIDES	OUTER	INNER C	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
6+8 x GN 1/1 80mm spacing	W: 525mm D: 810mm H: 1605mm	W: 330mm D: 540mm H: 510mm	W: 330mm D: 540mm H: 670mm	80 kg	<p>Exterior walls: ABS plastic.</p> <p>Inner container: Welded container in stainless steel.</p> <p>Guides: Stainless steel, pressed from the inner container.</p> <p>Insulation: Polyurethane foam.</p> <p>Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p>Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p>Top frame: Stainless steel and PVC corners.</p> <p>Trolley frame: Reject list of galvanized steel coated with PVC. C: Efficient compact chillers with electronic temperature control AA120/180W, insulation class IP44.</p> <p>F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/550W. CE and S mark.</p>
<p>AA120/180W + 230V/550W Product number: 122251-ZCF SDX Thermobox CF210 (6+8 GN 1/1) Single handed grip handle <i>Additional pull handles on the sides, at the back, are included</i></p> <p>Product number: 122251-XCF SDX Thermobox CF210 (6+8 GN 1/1) Excenter lock <i>Additional pull handles on the sides, at the back, are included</i></p>					