



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
6+8 x GN 1/1 80mm spacing	80kg	AA120/245W + 230V/550W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER C	INNER F	GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 830mm H: 1605mm	W: 330mm D: 540mm H: 510mm	W: 330mm D: 540mm H: 670mm	INSULATION:	Polyurethane.
ADDITIONAL INFORMATION			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
Additional pull handles on the sides, at the back, are included.			WHEELS:	160 mm wheels, two brakeable and two fixed.
PRODUCT NUMBER			TOP FRAME:	A stable and protective frame with PVC corners.
122251-ZCF SDX Thermobox CF210 (6+8 GN 1/1) One grip handle			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
122251-XCF SDX Thermobox CF210 (6+8 GN 1/1) Eccentric lock			C:	Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55.
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT