



| | | | | |
|--|---------------------------------------|----------------|-------------------------|---|
| GUIDES | WEIGHT | EFFECT | EXTERIOR WALLS: | ABS plastic. |
| 12+12 x GN 1/1 80mm spacing | 114kg | 2 x 230V/1000W | INNER CONTAINER: | Welded container in stainless steel. |
| OUTER | INNER | | GUIDES: | Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg. |
| W: 930mm D: 770mm H: 1355mm | W: 330+330mm D: 540mm H: 1000mm | | INSULATION: | Polyurethane. |
| PRODUCT NUMBER | | | DOOR: | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. |
| 122048-ZF SDX Thermobox FF360 (12+12 GN 1/1) One grip handle | | | WHEELS: | 160 mm wheels, two brakeable and two fixed. |
| | | | TOP FRAME: | A stable and protective frame with PVC corners. |
| | | | TROLLEY FRAME: | Reject list of stainless steel coated with PVC. |
| | | | F: | Efficient convection heating system, with electronic temperature control. IP55 rated. |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT