PRODUCTSHEET SDX® THERMOBOX® C-SERIES REV. 20230614SDX



C210 \*



GUIDES	WEIGHT EFFECT		EXTERIOR WALLS:	ABS plastic.
14 x GN 1/1 80mm spacing	75kg	230V/245W	EXTERIOR WALLS.	Abs plastic.
			INNER CONTAINER:	Welded container in stainless steel.
OUTER INNER			GUIDES:	Stainless steel, pressed from the inner container.
W: 525mm	W: 330mm	W: 330mm D: 540mm H: 1160mm		Maximum load per pair of guides is 30 kg.
D: 830mm H: 1515mm				Polyurethane.
Additional pull handles on the sides, at the back, are included.			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
PRODUCT NUMBER			WHEELS:	160 mm wheels, two brakeable and two fixed.
122209-ZC SDX Thermobox C210 (14 GN 1/1) One grip handle			TOP FRAME:	A stable and protective frame with PVC corners.
122209-XC SDX Thermobox C210 (14 GN 1/1) Eccentric lock		C:	Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55.	

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT

