

SF240 **≡**



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
8+8 x GN 1/1 80mm spacing	90kg	Neutral + 230V/1000W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER S	INNER F	GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 930mm D: 770mm H: 1215mm	W: 330mm D: 540mm H: 670mm	W: 330mm D: 540mm H: 670mm	INSULATION:	Polyurethane.
PRODUCT NUMBER		DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.	
122066-ZSF SDX Thermobox SF240 (8+8 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			S:	Neutral, insulation class IP55.
			F:	Efficient convection heating system, with electronic temper- ature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT