



TRAYSERVE K8 *

BASED ON THE STANDARD K180 ECO MODEL



GUIDES	WEIGHT	EFFECT	TEMPERATURE RANGE:	1 - 9°C
8 x GN 1/1 115mm spacing	77 kg	230V/190W	EXTERIOR WALLS:	ABS plastic.
OUTER	INNER		INNER CONTAINER:	Welded container in stainless steel.
W: 525mm D: 770mm H: 1575mm	W: 330mm D: 540mm H: 1000mm		GUIDES:	Aluminium, riveted to inner container
ADDITIONAL INFORMATION			INSULATION:	Polyurethane.
Additional pull handles on the sides, at the back, are included.			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
PRODUCT NUMBER			WHEELS:	160 mm wheels, two brakeable and two fixed.
122954-ZTS SDX®THERMOBOX® Trayserve K8 (8 GN 1/1 115D) One grip handle			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.
			K:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT