

**THERMOBOX<sup>®</sup> CC420 – ACTIVE COOLING**


| GUIDES   | OUTER  | INNER  | WEIGHT       | TECHNICAL SPECIFICATIONS   |
|--|--|--|--------------|--|
| <b>14+14 x GN 1/1</b><br>80mm spacing  | <b>W: 920mm</b><br><b>D: 825mm</b><br><b>H: 1515mm</b> | <b>W: 330+330mm</b><br><b>D: 540mm</b><br><b>H: 1160mm</b> | <b>75 kg</b> | <b>Exterior walls:</b> ABS plastic.<br><b>Inner container:</b> Welded container in stainless steel.<br><b>Guides:</b> Stainless steel, pressed from the inner container.<br><b>Insulation:</b> Polyurethane foam.<br><b>Door:</b> Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.<br><b>Wheels:</b> Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.<br><b>Top frame:</b> Stainless steel and PVC corners.<br><b>Trolley frame:</b> Rejact list of galvanized steel coated with PVC. <b>C:</b> Efficient compact chillers with electronic temperature control AA120, 27V DC. 230V/245W AC, insulation class IP44. |
| <b>Product number: 122265-ZC</b><br>SDX Thermobox C420 (14+14 GN 1/1) Single handed grip handle<br><br><b>Product number: 122265-XC</b><br>SDX Thermobox C420 (14+14 GN 1/1) Excenter lock |  |  |              |  |