PRODUCTSHEET SDX® THERMOBOX® C-SERIES REV. 20230614SDX

## **SDX** THERMOBOX





GUIDES	WEIGHT EFFECT		EXTERIOR WALLS: ABS plastic.	
14+14 x GN 1/1 80mm spacing	150kg	2 x 230V/245W		
			INNER CONTAINER:	Welded container in stainless steel.
OUTER INNER			Stainless steel, pressed from the inner container.	
W: 935mm	n D: 540mm		GUIDES:	Maximum load per pair of guides is 30 kg.
D: 830mm H: 1515mm			INSULATION:	Polyurethane.
Additional pull handles on the sides, at the back, are included.			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
PRODUCT NUMBER			WHEELS:	160 mm wheels, two brakeable and two fixed.
122265-ZC SDX Thermobox CC420 (14+14 GN 1/1)One grip handle		TOP FRAME:	A stable and protective frame with PVC corners.	
			C:	Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT

