

# SDX® THERMOBOX®

# KK300 ECO \*



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
10+10 x GN 1/1 80mm spacing	160kg	2 x 230V/190W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER		GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 930mm D: 770mm H: 1400mm	W: 330+330mm D: 540mm H: 825mm		INSULATION:	Polyurethane.
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122273-ZKK SDX Thermobox KK300 ECO (10+10 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			K:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT