

SDX® THERMOBOX®

CE180



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
4+8x GN 1/1 80mm spacing	70kg	AA120/245W + 230V/650W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER K	INNER F	GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 830mm H: 1445mm	W: 330mm D: 540mm H: 350mm	W: 330mm D: 540mm H: 670mm	INSULATION:	Polyurethane.
PRODUCT NUMBER			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122203-ZCE SDX Thermobox CE180 (4+8 GN 1/1) One grip handle			WHEELS:	160 mm wheels, two brakeable and two fixed.
122203-XCE SDX Thermobox CE180 (4+8 GN 1/1) Eccentric lock			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Reject list of stainless steel coated with PVC.
			C:	Efficient compact chillers with electronic temperature control AA120, 27 V DC. Insulation class IP55.
			E:	Patented, efficient heating system, with electronic temperature control. Foil elements, insulation class IP55.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT