



KF180 ECO



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
4+8 x GN 1/1 80mm spacing	98kg	K: 230V/190W AC F: 230V/550W	INNER CONTAINER:	Welded container in stainless steel.
OUTER	INNER K	INNER F	GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 770mm H: 1665mm	W: 330mm D: 540mm H: 350mm	W: 330mm D: 540mm H: 670mm	INSULATION:	Polyurethane.
ADDITIONAL INFORMATION			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
Additional pull handles on the sides, at the back, are included.			WHEELS:	160 mm wheels, two brakeable and two fixed.
PRODUCT NUMBER			TOP FRAME:	A stable and protective frame with PVC corners.
122214-ZKF SDX Thermobox KF180 ECO (4+8 GN 1/1) One grip handle			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.
			K:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated
			F:	Efficient convection heating system. Digital temperature regulation. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT