

## THERMOBOX® FF210 – CONVECTION HEATING



| GUIDES   | OUTER                             | INNER                                | WEIGHT | TECHNICAL SPECIFICATIONS   |
|--|-----------------------------------|--------------------------------------|--------|--|
| 8+6 x GN 1/1<br>80mm spacing   | W: 525mm<br>D: 750mm<br>H: 1605mm | W: 330mm<br>D: 540mm<br>H: 670+510mm | 70 kg  | <p><b>Exterior walls:</b> ABS plastic.</p> <p><b>Inner container:</b> Welded container in stainless steel.</p> <p><b>Guides:</b> Stainless steel, pressed from the inner container.</p> <p><b>Insulation:</b> Polyurethane foam.</p> <p><b>Door:</b> Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p><b>Wheels:</b> Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p><b>Top frame:</b> Stainless steel and PVC corners.</p> <p><b>Trolley frame:</b> Reject list of stainless steel coated with PVC.</p> <p><b>F:</b> Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/550W. CE mark.</p> |
| <p>2 x 230V/550W</p> <p><b>Product number:</b> 122135-ZF<br/>SDX Thermobox FF210 (8+6 GN 1/1) Single handed grip handle<br/><i>Additional pull handles on the sides, at the back, are included</i></p> <p><b>Product number:</b> 122135-XF<br/>SDX Thermobox FF210 (8+6 GN 1/1) Excenter lock<br/><i>Additional pull handles on the sides, at the back, are included</i></p> |                                   |                                      |        |  |