



# TRAYSERVE F9

BASED ON THE STANDARD F210 MODEL



GUIDES	WEIGHT	EFFECT	TEMPERATURE RANGE:	40 - 90°C
9 x GN 1/1 115mm spacing	64kg	230V/1000W	EXTERIOR WALLS:	ABS plastic.
OUTER	INNER		INNER CONTAINER:	Welded container in stainless steel.
W: 525mm D: 770mm H: 1515mm	W: 330mm D: 540mm H: 1160mm		GUIDES:	Aluminium, riveted to inner container
ADDITIONAL INFORMATION			INSULATION:	Polyurethane.
Additional pull handles on the sides, at the back, are included.			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
PRODUCT NUMBER			WHEELS:	160 mm wheels, two brakeable and two fixed.
<b>122957-ZTS</b> SDX®THERMOBOX® Trayserve F9 (9 GN 1/1 115D) One grip handle			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT