



# K60 ECO \*



<b>GUIDES</b>		<b>WEIGHT</b>	<b>EFFECT</b>	<b>EXTERIOR WALLS:</b>	ABS plastic.
4 x GN 1/1 80mm spacing		65 kg	230V/190W	<b>INNER CONTAINER:</b>	Welded container in stainless steel.
<b>OUTER</b>		<b>INNER</b>		<b>GUIDES:</b>	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.
W: 525mm D: 770mm H: 925mm		W: 330mm D: 540mm H: 350mm		<b>INSULATION:</b>	Polyurethane.
<b>PRODUCT NUMBER</b>				<b>DOOR:</b>	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
122206-ZK SDX Thermobox K60 ECO (4 GN 1/1) One grip handle				<b>WHEELS:</b>	160 mm wheels, two brakeable and two fixed.
122206-XK SDX Thermobox K60 ECO (4 GN 1/1) Eccentric lock				<b>TOP FRAME:</b>	A stable and protective frame with PVC corners.
				<b>TROLLEY FRAME:</b>	Reject list of stainless steel coated with PVC.
				<b>K:</b>	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT