



GUIDES	WEIGHT	EFFECT	TARGET TEMPERATURE	S: -	F: 80°C
4+10 x GN 1/1 80mm spacing	80kg	Neutral + 230V/1000W	TEMPERATURE RANGE:	S: -	F: 40 - 90°C
			EXTERIOR WALLS:	ABS plastic.	
			INNER CONTAINER:	Welded container in stainless steel.	
			GUIDES:	Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg.	
			INSULATION:	Polyurethane.	
			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.	
			WHEELS:	160 mm wheels, two brakeable and two fixed.	
			TOP FRAME:	A stable and protective frame with PVC corners.	
			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.	
			S:	Neutral, insulation class IP55.	
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.	
ADDITIONAL INFORMATION					
Additional pull handles on the sides, at the back, are included.					
PRODUCT NUMBER					
122065-ZSF SDX Thermobox SF210 (4+10 GN 1/1) One grip handle					
122065-XSF SDX Thermobox SF210 (4+10 GN 1/1) Eccentric lock					

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT