

THERMOBOX® KFF390 – COMPRESSOR COOLING AND CONVECTION HEATING COMBINATION


GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
6+10+10 x GN 1/1 80mm spacing	W: 1360mm D: 770mm H: 1180mm	W: 330mm D: 540mm H: 510mm	W: 330+330mm D: 540mm H: 830mm	170 kg	<p>Exterior walls: ABS plastic.</p> <p>Inner container: Welded container in stainless steel.</p> <p>Guides: Stainless steel, pressed from the inner container.</p> <p>Insulation: Polyurethane foam.</p> <p>Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p>Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p>Top frame: Aluminium and PVC corners.</p> <p>Trolley frame: Reject list of stainless steel coated with PVC.</p> <p>K: Efficient convection cooling with electronic temperature control 230V/190W, insulation class IP44.</p> <p>F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE-mark.</p>
230V/190W AC + 2x230V/1000W Product number: 122239-ZKFF SDX Thermobox KFF390 (6+10+10 GN 1/1) Single handed grip handle					