



TRAYSERVE FF16

BASED ON THE STANDARD FF360 MODEL



GUIDES	WEIGHT	EFFECT	TEMPERATURE RANGE:	40 - 90°C
8+8 x GN 1/1 115mm spacing	114kg	2 x 230V/1000W	EXTERIOR WALLS:	ABS plastic.
OUTER	INNER LEFT	INNER RIGHT	INNER CONTAINER:	Welded container in stainless steel.
W: 930mm D: 770mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	GUIDES:	Aluminium, riveted to inner container
PRODUCT NUMBER			INSULATION:	Polyurethane.
122953-ZTS SDX®THERMOBOX® Trayserve FF16 (8+8 GN 1/1 115D) One grip handle			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS:	160 mm wheels, two brakeable and two fixed.
			TOP FRAME:	A stable and protective frame with PVC corners.
			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT