



| GUIDES  | WEIGHT                               | EFFECT         | EXTERIOR WALLS:  | ABS plastic.  |
|---|--------------------------------------|----------------|------------------|---|
| 10+10 x GN 1/1<br>80mm spacing                                | 120kg                                | 2 x 230V/1000W | INNER CONTAINER: | Welded container in stainless steel.  |
| OUTER   | INNER                                |                | GUIDES:          | Stainless steel, pressed from the inner container.<br>Maximum load per pair of guides is 30 kg. |
| W: 930mm<br>D: 770mm<br>H: 1180mm                             | W: 330+330mm<br>D: 540mm<br>H: 830mm |                | INSULATION:      | Polyurethane.   |
| PRODUCT NUMBER  |                                      |                | DOOR:            | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.          |
| 122133-ZF<br>SDX Thermobox FF300 (8+8 GN 1/1) One grip handle |                                      |                | WHEELS:          | 160 mm wheels, two brakeable and two fixed.   |
|   |                                      |                | TOP FRAME:       | A stable and protective frame with PVC corners.   |
|   |                                      |                | TROLLEY FRAME:   | Reject list of stainless steel coated with PVC.   |
|   |                                      |                | F:               | Efficient convection heating system, with electronic temperature control. IP55 rated.           |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT