



GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
8+8 x GN 1/1 80mm spacing	W: 930mm D: 750mm H: 1245mm	W: 330mm D: 540mm H: 670mm	W: 330mm D: 540mm H: 670mm	132 kg	<p>Exterior walls: ABS plastic.</p> <p>Inner container: Welded container in stainless steel.</p> <p>Guides: Stainless steel, pressed from the inner container.</p> <p>Insulation: Polyurethane foam.</p> <p>Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p>Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Top frame: Stainless steel and PVC corners.</p> <p>Trolley frame: Rejected list of galvanized steel coated with PVC.</p> <p>K: Efficient convection cooling with electronic temperature control 230V/190W, insulation class IP44.</p> <p>F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/550W. CE mark.</p>
<p>230V/190W AC + 230V/550W</p> <p>Product number: 122262-ZKF</p> <p>SDX Thermobox KF240 ECO (8+8 GN 1/1) Single handed grip handle</p>					