PRODUCTSHEET SDX® THERMOBOX® F-SERIES REV. 20230614SDX







| GUIDES | WEIGHT | EFFECT |
|------------------------------|--------------|---------------|
| 6+6 x GN 1/1 80mm spacing | 65kg | 2 x 230V/550W |
| OUTER | INNER | |
| W: 525mm | W: 330mm | |
| D: 770mm | D: 540mm | |
| H: 1445mm | H: 510+510mm | |
| PRODUCT NUMBER | | |

122134-ZF

SDX Thermobox FF180 (6+6 GN 1/1) One grip handle

122134-XF

SDX Thermobox FF180 (6+6 GN 1/1) Eccentric lock

| EXTERIOR WALLS: | ABS plastic. |
|------------------|---|
| INNER CONTAINER: | Welded container in stainless steel. |
| GUIDES: | Stainless steel, pressed from the inner container. Maximum load per pair of guides is 30 kg. |
| INSULATION: | Polyurethane. |
| DOOR: | Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. |
| WHEELS: | 160 mm wheels, two brakeable and two fixed. |
| TOP FRAME: | A stable and protective frame with PVC corners. |
| TROLLEY FRAME: | Reject list of stainless steel coated with PVC. |
| F: | Efficient convection heating system, with electronic temperature control. IP55 rated. |

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT

