REV. 20230614SDX PRODUCTSHEET SDX® THERMOBOX® K-SERIES

## **SDX** THERMOBOX

## **KK360 ECO** \*



GUIDES	WEIGHT	EFFECT	EXTERIOR WALLS:	ABS plastic.
12+12 x GN 1/1 80mm spacing	170kg	2 x 230V/190W	INNER CONTAINER:	Welded container in stainless steel.
OUTER INNER		GUIDES:	Stainless steel, pressed from the inner container.  Maximum load per pair of guides is 30 kg.	
W: 930mm D: 770mm H: 1575mm	W: 330+330mm D: 540mm H: 1000mm		INSULATION:	Polyurethane.
Additional pull handles on the sides, at the back, are included.			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.
			WHEELS:	160 mm wheels, two brakeable and two fixed.
PRODUCT NUMBER			TOP FRAME:	A stable and protective frame with PVC corners.
122271-ZKK SDX Thermobox KK360 ECO (12+12 GN 1/1) One grip handle		TROLLEY FRAME:	Reject list of stainless steel coated with PVC.	
			к:	Efficient compressor refrigeration. Eco-friendly refrigerant (R290A) Low-noise, RPM-controlled fans. Digital temperature regulation. IP44 rated

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT